

GORDON INTERNATIONAL PTY LTD

Tel: (612) 9938 4493

Fax: (612) 9938 4496

sales @ gordon.org.au

MASKING TAPE TECHNICAL DATA SHEET

Backing: Crepe Paper
Adhesive: Solvent-Based Natural Rubber

Properties	# 57W	# 63W	# 63CW	# 67W	# 67CW
Total Weight	87±3 g/m ²	89±3 g/m ²	89±3 g/m ²	94±3 g/m ²	94±3 g/m ²
Total Thickness	5.2±0.6Mil (0.132±0.015mm)	5.3±0.6Mil (0.135±0.015mm)	5.2±0.6 Mil (0.132±0.015mm)	5.8±0.6 Mil (0.147±0.015mm)	5.8±0.6 Mil (0.147±0.015mm)
Steel Adhesion (ASTM D 3330)*	0.60 kg/in (21.2oz/in)	0.70 kg/in (24.7 oz/in)	0.85 kg/in (30.0 oz/in)	0.90 kg/in (31.8 oz/in)	0.85 kg/in (30.03 oz/in)
Tensile Strength (ASTM D 3759)*	20±3lbs/in. (7.7~10.4kg/in)	20±3lbs/in. (7.7~10.4kg/in)	20±3lbs/in. (7.7~10.4kg/in)	20±3lbs/in. (7.7~9.1kg/in)	20±3lbs/in. (7.7~9.1kg/in)
Elongation (ASTM D 3759)*	11±4%	11±4%	10±3%	11±4%	10±3%
Initial Tack (PSTC-6)	<70mm	<70mm	<100mm	<50mm	<70mm
Max. Temp. Resistance	80°C / 176°F	80°C / 176°F	95°C / 203°F	80°C / 176°F	95°C / 203°F
Application Temp.	60°C / 140°F	60°C / 140°F	80°C / 176°F	60°C / 140°F	80°C / 176°F
Application	Bundling, Packaging Indoor Painting Splicing	Bundling, Packaging Indoor Painting Splicing	Bundling, Packaging Indoor Painting	Bundling, Packaging Indoor Painting Splicing	Automobile Painting Indoor Painting
Colors Available	Natural & Yellow	Natural & Yellow	Natural & Yellow	Natural & Yellow	Natural & Yellow
Properties	# 81	# 111	# 59G	# 70B	
Total Weight	96±3 g/m ²	99±3 g/m ²	89±3 g/m ²	102±3 g/m ²	
Total Thickness	5.8±0.6 Mil (0.147±0.015mm)	6.1±0.6 Mil (0.155±0.015mm)	4.7±0.6 Mil (0.119±0.015mm)	5.2±0.6 Mil (0.132±0.015mm)	
Steel Adhesion (ASTM D 3330)*	0.95 kg/in (33.6 oz/in)	1.0kg/in (35.3 oz/in)	0.50kg/in (17.6 oz/in)	0.55kg/in (19.4 oz/in)	
Tensile Strength (ASTM D 3759)*	20±3lbs/in. (7.7~9.1kg/in)	20±3lbs/in. (7.7~9.1kg/in)	22.9±3lbs/in. (9.0~11.7kg/in)	27.8±3lbs/in. (11.2~13.9kg/in)	
Elongation (ASTM D 3759)*	10±3%	10±3%	10±3%	10±3%	
Initial Tack (PSTC-6)	<80mm	<80mm	<80mm	<60mm	
Max. Temp. Resistance	95°C / 203°F	110°C / 230°F	95°C / 203°F	95°C / 203°F	
Application Temp.	80°C / 176°F	95°C / 203°F	80°C / 176°F	80°C / 176°F	
Application	Automobile Painting Resistor Belting	Automobile Painting Resistor Belting	Outdoor Painting	Outdoor Painting	
Colors Available	Natural & Yellow	Natural & Yellow	Green	Blue	

Warranty of Masking Tape Product to meet Specifications

Non-Curing - Six Months Warranty - Jumbo or Finished Rolls on vertical position stored without direct sun contact temperature of 23oC+2oC and humidity of 50%+5%.

Curing - Twelve Months Warranty - Jumbo or Finished Rolls on vertical position stored without direct sun contact at temperature of 23oC+2oC and humidity of 50%+5%.