

Gordon International Marketing Steel strapping Specification

| Grade | Width | Thickness | Colour | Coil Winding | Elongation | Break Strain (kg) | Tensile Strength (MPA) | Yield Meter s (kg) | Coil Size | Packing Coils Skid (pallet) | Coil Weight (kg) | Total Weight per pallet (kg) | Pallets Size(mm) | | | Pallet Weight (kg) |
|-------|--------|-----------|---------------|------------------|------------|-------------------|------------------------|--------------------|------------------|-----------------------------|------------------|------------------------------|------------------|-----|-----|--------------------|
| | | | | | | | | | | | | | L | W | H | |
| RD | 12.7mm | 0.40mm | Black-Painted | Mini Ribbon | 2-3% | 440 | 850 | 24.80 | D:200mm OD:420mm | 40 | 10+/-1 | 363-463 | 400 | 400 | 100 | 3 |
| RD | 12.7mm | 0.50mm | Black-Painted | Mini Ribbon | 2-3% | 551 | 850 | 19.67 | D:200mm OD:420mm | 40 | 10+/-1 | 363-463 | 400 | 400 | 100 | 3 |
| RD | 15.9mm | 0.50mm | Black-Painted | Mini Ribbon | 2-3% | 690 | 850 | 15.61 | D:200mm OD:420mm | 36 | 13+/-1 | 435-507 | 400 | 400 | 100 | 3 |
| RD | 19.0mm | 0.50mm | Black-Painted | Mini Ribbon | 2-3% | 824 | 850 | 13.15 | D:200mm OD:420mm | 30 | 15+/-1 | 423-483 | 400 | 400 | 100 | 3 |
| RD | 19.0mm | 0.56mm | Black-Painted | Mini Ribbon | 2-3% | 923 | 850 | 11.56 | D:200mm OD:420mm | 30 | 15+/-1 | 423-483 | 400 | 400 | 100 | 3 |
| RD | 15.9mm | 0.45mm | Black-Painted | Rope/ Mill wound | 2-3% | 621 | 850 | 17.33 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| RD | 15.9mm | 0.45mm | Black-Painted | Ribbon Wound | 2-3% | 621 | 850 | 17.33 | D:305mm OD:590mm | 30 | 25+/-1 | 726-786 | 580 | 580 | 100 | 6 |
| RD | 15.9mm | 0.58mm | Black-Painted | Rope/ Mill wound | 2-3% | 804 | 850 | 13.73 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| RD | 15.9mm | 0.58mm | Black-Painted | Ribbon Wound | 2-3% | 804 | 850 | 13.73 | D:305mm OD:590mm | 30 | 25+/-1 | 726-786 | 580 | 580 | 100 | 6 |
| HT | 15.9mm | 0.58mm | Black-Painted | Rope/ Mill wound | 4-6% | 847 | 900 | 13.73 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| HT | 15.9mm | 0.58mm | Black-Painted | Ribbon Wound | 4-6% | 847 | 900 | 13.73 | D:305mm OD:590mm | 30 | 25+/-1 | 726-786 | 580 | 580 | 100 | 6 |
| RD | 19.0mm | 0.56mm | Black-Painted | Rope/ Mill wound | 2-3% | 923 | 850 | 11.56 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| RD | 19.0mm | 0.56mm | Black-Painted | Ribbon Wound | 2-3% | 923 | 850 | 11.56 | D:305mm OD:590mm | 25 | 30+/-1 | 731-781 | 580 | 580 | 100 | 6 |
| RD | 19.0mm | 0.50mm | Black-Painted | Rope/ Mill wound | 2-3% | 824 | 850 | 13.15 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| RD | 19.0mm | 0.50mm | Black-Painted | Ribbon Wound | 2-3% | 824 | 850 | 13.15 | D:305mm OD:590mm | 25 | 30+/-1 | 731-781 | 580 | 580 | 100 | 6 |
| RD | 19.0mm | 0.60mm | Black-Painted | Rope/ Mill wound | 2-3% | 989 | 850 | 11.17 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| RD | 19.0mm | 0.60mm | Black-Painted | Ribbon Wound | 2-3% | 989 | 850 | 11.17 | D:305mm OD:590mm | 25 | 30+/-1 | 731-781 | 580 | 580 | 100 | 6 |
| HT | 19.0mm | 0.63mm | Green-Painted | Rope/ Mill wound | 4-6% | 1099 | 900 | 10.37 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| HT | 19.0mm | 0.63mm | Green-Painted | Ribbon Wound | 4-6% | 1099 | 900 | 10.37 | D:305mm OD:590mm | 25 | 30+/-1 | 731-781 | 580 | 580 | 100 | 6 |
| HT | 19.0mm | 0.80mm | Green-Painted | Rope/ Mill wound | 4-6% | 1396 | 900 | 8.38 | D:406mm OD:600mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |
| HT | 19.0mm | 0.80mm | Green-Painted | Ribbon Wound | 4-6% | 1396 | 900 | 8.38 | D:305mm OD:590mm | 25 | 30+/-1 | 731-781 | 580 | 580 | 100 | 6 |
| HT | 32.0mm | 0.80mm | Green-Painted | Ribbon Wound | 4-6% | 2351 | 900 | 5.02 | D:305mm OD:590mm | 14 | 41-48 | 580-678 | 580 | 580 | 100 | 6 |