

## Hi-TECH GUMMED TAPE H40 Specification Natural and White

### CONSTRUCTION

<b>Top Sheet</b>	25 # / Ream High Tensile Virgin Kraft
<b>Bottom Sheet</b>	20 # / Ream MG Natural High Tensile Virgin Kraft
<b>Laminant</b>	Non –Asphaltic Type Polypropylene Based Polymer Non-Staining, Flexible, Water-Resistant Complies with; FDA – CFR 175.105
<b>Reinforcement</b>	3-way "fiberglass" Reinforcement pattern Lengthwise threads with Diamond cross pattern <b>MD:</b> 75 Yarn, Fiberglass Pattern with ½" Parallel Spacing (Machine Direction) (1-1-1-1-1) 6 Thread Groups <b>CMD</b> 150 Yarn, Fiberglass Diamond Pattern, Less then 1¼" (Cross Machine Direction) spacing between parallel threads
<b>Adhesive</b>	Smooth even coating of Special "High Tack" Water Activated Modified Corn Starch Based Adhesive System.
<b>Caliper</b>	5.7 Mils to 7.3Mils

### PERFORMANCE

<b>Tensile</b>	(Typical): (TAPPIT-404) <b>MD</b> (Machine Direction): .....68 #/in. <b>CMD</b> (Cross Machine Direction): .....28 #/in. <b>NOTE:</b> Bleached top sheet tests slightly lower in Tensile Than Natural Top Sheet
----------------	--

### SIZE and PACKAGING

* Sizes	Rolls / Carton	Cartons / Pallet	* Sizes	Rolls / Carton	Cartons / Pallet
2in. x 375ft. 51mm x 114 m.	12	75	2.83 in. x 375ft. 72 mm x 114 m.	8	75
2½in. x 360ft. 64 mm x 110 m.	10	75	2.83 in. x 450ft. 72 mm x 137 m.	10	60
3in. x 375ft. 76 mm x 114 m.	8	75	2.83 in. x 500ft. 72 mm x 152 m.	6	90
3in x 450ft. 76 mm x 137 m.	10	60	2.83 in. x 500ft. 72 mm x 152 m.	10	60
3in. x 600ft. 76 mm x 183 m.	5	120	2.83 in. x 600ft. 72 mm x 183 m.	5	120
3in. x 600ft. 76 mm x 183 m.	10	60	2.83 in. x 600ft. 72 mm x 183 m.	10	60

\* Other Widths and Lengths Available

ALL PALLETS are stretch wrapped for secure clean transit and storage

PRINTED TAPES are printed with WATER-BASED INK (HEAVY METAL FREE) and are ENVIRONMENTALLY FRIENDLY.