

COBRA TAPE Specifications

Natural

CONSTRUCTION

Top Sheet	25 # / Ream Natural High Tensile Virgin Kraft
Bottom Sheet	20 # / Ream MG Natural High Tensile Virgin Kraft
Laminant	Non –Asphaltic Type Polypropylene Based Polymer Non-Staining, Flexible, Water-Resistant Complies with; FDA – CFR 175.105
Reinforcement	3-way "fiberglass" Reinforcement pattern Lengthwise threads with Diamond cross pattern MD: 110 Yarn, Fiberglass Pattern with 5/8" Spacing (Machine Direction) (1-1-1-1) 5 Thread Groups CMD 150 Yarn, Fiberglass Diamond Pattern, Less then 1¼" (Cross Machine Direction) spacing between parallel threads
Adhesive	Smooth even coating of Special "High Tack" Water Activated, Modified Corn Starch Based Adhesive System.
Caliper	4.9 Mils to 7.3 Mils

PERFORMANCE

Tensile	(Typical): (TAPPIT-404) Complies with GIA (Gummed Industry Association) Standards for "Light Duty Reinforced Sealing tape". Meets or Exceeds GIA Minimum requirements in pounds / inch. (Light Duty Min. Standards: MD-57 #/rm. ; CMD-27 #/in.) MD (Machine Direction): 62 #/in. CMD (Cross Machine Direction): 27 #/in.
----------------	---

SIZE and PACKAGING

* Sizes	Rolls / Carton	Cartons / Pallet	* Sizes	Rolls / Carton	Cartons / Pallet
2in. x 375ft. 51mm x 114 m.	12	75	2.83 in. x 375ft. 72 mm x 114 m.	8	75
2½in. x 360ft. 64 mm x 110m.	10	75	2.83 in. x 450ft. 72 mm x 137 m.	10	60
3in. x 375ft. 76 mm x 114 m.	8	75	2.83 in. x 500ft. 72 mm x 152 m.	6	90
3in x 450ft. 76 mm x 137m.	10	60	2.83 in. x 500ft. 72 mm x 152 m.	10	60
3in. x 600ft. 76 mm x 183m.	5	120	2.83 in. x 600ft. 72 mm x 183 m.	5	120
3in. x 600ft. 76 mm x 183m.	10	60	2.83 in. x 600ft. 72 mm x 183 m.	10	60

* CALL CUSTOMER SERVICE for Widths and Lengths available
 ALL PALLETS are stretch wrapped for secure clean transit and storage
 PRINTED TAPES are printed with WATER-BASED INK (HEAVY METAL FREE) and are ENVIRONMENTALLY FRIENDLY.