

## JETTACK GUMMED SEALING TAPE Specification Sheet

This is a heat sealing tape made for sealing flat folded paper sacks / bags. Various grades are available with paper weights of 120g/m<sup>2</sup> and 150g/m<sup>2</sup> with 30g or 45g hotmelt adhesive. A new innovation which combines the sealing process with the addition of a tear strip tape. It involves adhering a red self adhesive strip to the Jettack tape before sealing it. It is recommended that one of the below tapes is used for this application.

### (\*E-150 & 1/150M)

Item No. 05 150 410 0	E-150 JETTACK GUMMED SEALING TAPE
Colour	White / Brown
Structure	Kraftliner Duplex 150g/m <sup>2</sup> +/-8%
Tensile Strength / Width	Machine Direction 12, 3kN/m
In Line with DIN EN ISO 1924-2	Cross Direction 5,2 kN/m
Coating / Gumming	HOTMELT 30g (JETTACK) Melting Point in line with DIN 52011 between 80°C - 110°C
Width of Roll	mm +/- 1mm
Length	M +/- 2%
Winding	Coating Outside
Cardboard Core	70mm

Item No. 05 150 400 0	1/150M JETTACK GUMMED SEALING TAPE
Colour	Brown
Structure	Kraftliner Brown, 150g/m <sup>2</sup> +/-8%
Tensile Strength / Width	Machine Direction 12,0 kN/m
In Line with DIN EN ISO 1924-2	Cross Direction 6,0 kN/m
Gumming	HOTMELT (JETTACK) Melting Point in line with DIN 52011 between 80 – 110 70°C
Width of Roll	mm +/- 1mm
Length	M +/- 2%
Winding	Coating Outside
Cardboard Core	70mm