

## SILICONE RUBBER COATED GLASS FABRICS

Style	Coated Sides	Nominal Thickness (mm)	Weight (g / m <sup>2</sup> )	Tensile Strength (N / cm)	Color
SIL - 020 W	BOTH SIDE	0,23	340	260	White
SIL - 020 R	BOTH SIDE	0,23	340	260	Red
SIL - 025 W	BOTH SIDE	0,28	400	400	White
SIL - 025 R	BOTH SIDE	0,28	400	400	Red
SIL - 035 W	BOTH SIDE	0,35	520	400	White
SIL - 035 R	BOTH SIDE	0,35	520	400	Red
SIL - 056 W	BOTH SIDE	0,56	700	760	White
SIL - 056 R	BOTH SIDE	0,56	700	760	Red
SIL - 076 W	BOTH SIDE	0,76	1100	800	White

\* On request, above products can be produced also with one side adhesive.

## SILICONE COATED GLASS FABRICS WITH ONE SIDE ADHESIVE

Style	Color	Width (mm)	Adhesive System	Protective Liner	Peel Adhesion N / cm
<b>FLAME RETARDANT PLASMA SPRAY MASKING TAPE</b>					
FR - 10AD	White	from 20 mm up to 1000 mm	Silicone PSA	Yellow PVC Liner	5,5
<b>HI - FRICTION TAPE</b>					
SIL - AD	Red	from 20 mm up to 1000 mm	Silicone PSA	Yellow PVC Liner	5,5

Note : Nominal thickness and tensile strength values are typical and are not intended as a specification minimum.  
Weight Tolerance g/m<sup>2</sup> = ±5%